06/Oct/2026

Notification of Discontinued Products

Dear Valued Customer,

We extend our sincere gratitude for your continued support of Panasonic. Your loyalty and dedication to Panasonic products have been vital to us.

After thorough consideration and evaluation, we regret to inform you that we will be discontinuing HX series 15mΩ of Conductive Polymer Aluminum Electrolytic Capacitors (SP-Cap).

We understand that this decision may cause inconvenience, and we apologize for any disruption it may bring to your operations. Our team is committed to minimizing any potential impact and assisting you throughout this transition.

Below are the details of the affected products:

Affected Product	**HX series 15mΩ:** EEFHX0D471R, EEFHX0E331R, EEFHX0E471R
Reason of Discontinuation	Integration to high reliability product
Schedule	NRND Schedule: from Oct 15, 2026 EOL Schedule: from Oct 15, 2027 Last Time Buy: Apr 15, 2028 Last Time Shipment: Oct 15, 2028
Suggested Alternatives	Please refer to the attached Excel file

We encourage you to reach out to us with any questions or concerns you may have regarding this announcement. Your satisfaction remains our top priority, and we are here to support you in finding suitable alternatives or addressing any challenges you may encounter.

Thank you for your understanding and continued partnership as we navigate this change together.

Best regards,

Panasonic Industry Europe

EOL Affected PN
EEFHX0D471R
EEFHX0E331R
EEFHX0E471R

EOL PN Secification
SP Cap / HX / 2V / 470µF / 125°C / 1000h / 7.3x4.3x1.9mm / ESR 15mOhm / ripple 5.1Arms
SP Cap / HX / 2.5V / 330µF / 125°C / 1000h / 7.3x4.3x1.9mm / ESR 15mOhm / ripple 5.1Arms
SP Cap / HX / 2.5V / 470µF / 125°C / 1000h / 7.3x4.3x1.9mm / ESR 15mOhm / ripple 5.1Arms

Alternative PN
EEFHX0D471R9
EEFHX0E331R9
EEFHX0E471R9

Alternative PN Specification
SP Cap / HX / 2V / 470µF / 125°C / 1000h / 7.3x4.3x1.9mm / ESR 9mOhm / ripple 6.3Arms
SP Cap / HX / 2.5V / 330µF / 125°C / 1000h / 7.3x4.3x1.9mm / ESR 9mOhm / ripple 6.3Arms
SP Cap / HX / 2.5V / 470µF / 125°C / 1000h / 7.3x4.3x1.9mm / ESR 9mOhm / ripple 6.3Arms